



ProColor Series1 Internal PC

The ProColor Internal PC feature allows you to have a brilliant high-definition display with a built-in classroom computer. Everything is simplified with our one device solution—from setup to usability.

The two available models of ProColor Series 1 Internal PC provides high-quality performance for our ProColor interactive flat panel display. The internal PC modules have a rich set of input and output connections .

- Full-featured solution runs MimioStudio™ classroom software to easily create and deliver engaging lessons.
- Complete integration with our other products, including our MimioMobile™ collaboration and assessment app.
- Connections: Two USB 3.0, one Mini DisplayPort, and one HDMI video port with up to 3840 x 2160 (4K or UHD) resolution.
- Eco-friendly with low power consumption.



To learn more, visit mimio.boxlight.com/procolor or call 866.972.1549.



Specifications

	I5 PROCESSOR	I7 PROCESSOR
Model	PROCOLOR-PCMODi5 v1.0	PROCOLOR-PCMODi7 v1.0
CPU	4th Generation Intel® Core™ i5 Processor	4th Generation Intel® Core™ i7 Processor
Socket	Intel® socket 1150 Support: Haswell	
RAM sockets	2 slots for DDR3 1333/1600MHz	
RAM installed	4 GB	up to 8 GB
Storage	128 SSD	
Graphics Card	Integrated Intel® HD Graphics	GeForce GT 730M
Sound Card	Integrated High Definition Audio Stereo	
Network Card	Integrated 10/100/1000M	
Wi-Fi	IEEE 802.11 ac(2.4G/5G)	
Bluetooth	Bluetooth 4.0	
CONNECTORS		
USB2.0/3.0	4 x USB 2 and 2 x USB 3	
Lan Port(RJ45)	1 x RJ-45	
VGA Out	1 x 15-pin DE-15	
Earphone Output	1 x 3.5 mm female	
Microphone Input	1 x 3.5 mm female	
Mini DisplayPort Output	1 x Mini Display Port (up to 4K2K resolution)	
HDMI Output	1 x High-Definition Multimedia Interface (up to 4K2K resolution)	
Heat-removal System	Dual Fan	
POWER		
Power Supply Mode	Internal Power Supply Module	
Power Requirements	100V-240V AC 50/60Hz	
Max Power	95W	
Standby Power	1.35W	
Physical Specifications		
Dimension L x W x H	233 mm x 217 mm x 33 mm (9.17 in. x 8.54 in. x 1.30 in.)	
Dimension(package) L x W x H	340 mm x 295 mm x 90 mm (13.39 in. x 11.61 in. x 3.54 in.)	
Net Weight	1.97 kg	
Gross Weight	2.36 kg	
ENVIRONMENTAL CONDITIONS		
Operation Temperature	0° to 40° C (32° to 104° F)	
Operation Humidity	10% - 90%	
Storage Temperature	-20° to 60° C (-4° to -76° F)	
Storage Humidity	10% - 90%	
ESD		
Contact Discharge	±6KV passed level A test (CB)/±8KV passed level B test (CB)	
Non-contact Discharge	±12KV passed level A test (CB)/±15KV passed level B test (CB)	

To learn more, visit mimio.boxlight.com/procolor or call 866.972.1549.